



Display Features Overview

Backlight	High bright LED sunlight readable (optional)
Finish	Grey or black powder coat standard
Mount	VESA rear mount standard optional 19 inch rack mount via bracket
User Controls	Front mounted sealed silicone
RoHS	Lead free RoHS compliant (optional)
Cooling	Natural Convection / Fan

Display Characteristics

Display size	24.1" diagonal
Resolution	1920 x 1200 colored pixels
Colors	16.7 million
Pixel Pitch	0.270mm(V) x 0.270mm(H)
Brightness	400 cd/m ²
Viewing Angle	+/-89 deg Horizontal axis : +/-89 deg Vertical axis
Contrast Ratio	1000:1
Power	External 100-240 VAC universal
Signal Connector	D-sub 15 pin & DVI
Input Signal	RGB standard analog
User Control	OSD (auto Saving)
Plug and Play	VESA DDC1/2B
Power Management	VESA DPMS compliant

Environmental Characteristics

Operating temp	-10 to 50 C	Non-operating	-40 to 60C
-----------------------	-------------	----------------------	------------

Mechanical Characteristics

Panel mount	NEMA 4 / VESA mount
--------------------	---------------------

Display Options

Rack mount	19 inch rack mount optional	High Bright	Up to 1000 nits
Touch Screen	Resistive, Capacitive, acoustic. RS232 or USB connection	DC power	8-16VDC & 18-36 VDC
Video input	NTSC PAL		

Tech Electronic Systems is a leading provider of flat panel display Solutions for our military with 21 years of experience in the field. Our extensive knowledge and expertise is now being used to support the Industrial sector with displays that are higher quality at commercial pricing. Our service department is available, but is hardly in use when you buy our displays, you are buying quality, performance and innovation.