

WATER TIGHT RUGGED DISPLAY



Display Features Overview	
Backlight	High bright LED sunlight readable (optional)
Anti Reflective Coating	AR coating minimizes specular reflections
Mount	VESA rear mount / flange mount design / 19 inch rack mount via bracket
Auto Position / Settings	Auto position resolution scaler from 640x480 to 1600x1200
RoHS	Lead free RoHS compliant (optional)
Cooling	Natural Convection / Fan

Display Characteristics			
Display Size	260 mm diagonal		
Resolution	1024 X 768 colored pixels		
Colors	262,144.00		
Active Area	(H)158.4mm x (W)211.2mm		
Pixel Pitch	.33mm(H) x 0.33mm(V)		
Brightness	150 cd/m ²		
Viewing Angle	Vertical: +/- 80 deg Horizontal: +/- 80 deg		
Contrast Ratio	800:1 Typical (typ)		
Response Time	35ms		
Sync Range	Horizontal: 30 kHz to 82 kHz		
Video non-interlaced	Min refresh rate 60 Hz / 72 Hz		
Controls	Front controlled with full dimming capabilities		
Power Input	115 AC 400 Hz		
Power Consumption	Less than 24 watts		
Data Inputs			
VGA	(x1) D-sub (optional)		
NTSC	Optional BNC input (optional)		
BNC	5-Wire RGBHV sync (optional)		
DVI-D	(x1) Dvi-D input (optional)		
INTERFACE	USB interface (optional)		
Mechanical Characteristics			
Bezel Dimensions	Outer dimensions (H)9.6" x (W) 12.5" (over all depth) 1.5"		
Weight	Less than 15 Lbs		
Cooling	Natural convection/ fan		
Environmental Characteristics (designed to)			
Shock	Mil-S-901D, Grade A, Class1 Type A Mil-STD-810E	Vibration	Mil-STD-167-1A, Type 1
EMI	Mil-STD-461E	Drip Proof	Mil-STD-810E
Sand & Dust	Mil-STD-810E	Operating temp	-25 to 55 C
Non-operating temp	-40 to 70C		
LCD Options			
NVIS	Compatible backlight systems	High Altitude	Explosive Atmosphere compatible
LED	Optional LED high bright backlight	Touch Screen	Acoustic, Capacitive, Resistive. USB or rs232
Low/High Temp	-40 to 60C operating	X-term	Integrated Pentium based